

IN THE CLAIMS:

1. (Currently amended) A heart actuator device for use in heart assist apparatus, the device including a paddle-like main body, the main body including a proximal heart-compressing wall, ~~which in use is~~ adapted to be affixed to at least a region of the heart, and a distal wall, ~~which in use is~~ adapted to be distal that region of the heart, and the proximal heart-compressing wall being movable in a direction relatively away from the distal wall, so as, in use to compress at least that region of the heart and being movable in a direction relatively toward the distal wall, so as, in use to decompress at least that region of the heart thereby assisting movement of the heart wall.
2. (Currently amended) A device according to claim 1 wherein said paddle-like main body includes two major walls secured to or integral with each other at the peripheral portions thereof, one of said major walls defining said proximal heart-compressing wall and the other defining said distal wall.
3. (Currently amended) A device according to claim 1 wherein said proximal heart compressing wall is generally curved inwardly towards the distal wall when in a normally relaxed condition.
4. (Original) A device according to claim 3 wherein the said distal wall is curved outwardly when in a normally relaxed condition.
5. (Currently amended) A device according to claim 1 including a chamber within the main body between the proximal heart-compressing wall and said distal wall and being adapted for the ingress or egress of fluid which causes the movement of the proximal heart-compressing wall.
6. (Currently amended) A device according to claim 1 wherein said main body is configured such that both the proximal heart-compressing wall and the distal wall are adapted to move in a direction relatively away from one another during compression of the heart.

7. (Currently amended) A device according to claim 6 wherein the proximal heart ~~compressing~~ wall and the distal wall of the main body are of ~~[[the]]~~ materials with different degrees of stiffness.

Claims 8-13 (Cancelled)

14. (Currently amended) A device according to claim 1 wherein the paddle-like main body is deformable so as to be capable of undergoing a change from a first configuration to a second configuration, said paddle-like main body including a shape memory material ~~which permits said deformation and subsequent return to its original shape.~~

15. (Previously presented) A device according to claim 1 wherein the main body includes a unitary structure formed of polyurethane or silicone, including reinforcement mesh or hardened material.

16. (Previously presented) A device according to claim 1 including means to monitor the electrical and mechanical activity of the heart.

17. (Original) A device according to claim 16 wherein the device is activated so as to boost the pump output of the heart.

18. (Currently amended) A device according to claim 17 wherein said monitoring means includes an electrocardiogram electrode operatively connected to at least a region of the surface of the heart and the electrical signals received from the electrodes are used to monitor the intrinsic electrical activity of the heart, these ~~theses~~ signals being also transmitted to a cardiometer for the detection of heart rate or beat-to-beat interval.

19. (Previously presented) A device according to claim 1 including a plurality of sensors adapted to measure the heart dimensions and movement or displacement of the chamber walls during excursion of the devices.

20. (Original) A device according to claim 19 wherein each sensor is a piezoelectric sensor.
21. (Original) A device according to claim 20 wherein each sensor is a sonomicrometer.
22. (Currently amended) A device according to claim 18 wherein said ECG electrode is integrated into said proximal heart-compressing wall.
23. (Currently amended) A device according to claim 19 wherein there are a plurality of said sensors operatively connected in selective positions to said proximal heart-compressing wall.
24. (Currently amended) A device according to claim 1 wherein said proximal heart compressing wall is configured so that the proximal heart-compressing surface generally conforms to the shape of that region of the heart to which it is fixed.
25. (Currently amended) A device according to claim 1 wherein said proximal heart compressing wall is adapted to be affixed to a region of the left ventricle of the heart.
26. (Currently amended) A device according to claim 1 wherein said proximal heart compressing wall is adapted to be fixed to a region of the right ventricle of the heart.
27. (Previously presented) A device according to claim 1 wherein the main body is at least initially affixed to the heart by straps.
28. (Previously presented) Heart assist apparatus including one or more heart actuator devices according to claim 1 which are adapted to be secured to a region or selected regions of the heart, said apparatus further including driving means in fluid communication with the chamber, said driving means including a controller and a power source.
29. (Original) Apparatus according to claim 28 wherein said driving means is a hydraulic driving apparatus.

30. (Original) Apparatus according to claim 28 wherein said driving means is a pneumatic driving means.

31. (Previously presented) Apparatus according to claim 28 wherein there is provided a plurality of said heart actuator devices operatively connected to selected regions of the heart.

32. (Currently amended) A method of assisting a failing heart using a heart actuator device according to claim 1, the method including the steps of:

- (a) positioning the proximal heart ~~compressing~~ wall of the device at least adjacent a region of the heart;
- (b) affixing the proximal heart ~~compressing~~ wall with the region of the heart; and
- (c) applying fluid pressure to the chamber of the device such that the proximal heart ~~compressing~~ wall compresses the heart wall in the region of the heart to which the device is affixed.

33. (Currently amended) A method of introducing a device according to claim 1 to the heart of a patient, the method including the steps of:

- (a) making an incision or puncture in the chest of a patient to allow access to the heart;
- (b) inserting the device through the incision or puncture;
- (c) affixing the proximal heart ~~compressing~~ wall to a region of the heart; and
- (d) applying fluid pressure to the chamber of the device such that the proximal heart ~~compressing~~ wall compresses the heart wall in the region of the heart to which the device is affixed.

34. (New) A heart actuator device for use in heart assist apparatus, the device including a paddle-like main body, the main body including a heart compressing wall, which in use is adapted to be affixed to at least a region of the heart, and a distal wall, which in use is adapted to be distal that region of the heart, and both the heart compressing wall and the distal wall being movable in a direction relatively away from one another during compression of the heart, so as, in use to compress at least that region of the heart thereby assisting movement of the heart wall, the heart compressing wall and the distal wall of the main body being of materials with different degrees of stiffness, the distal wall including a reinforcing material therein to provide for a greater degree of stiffness relative to the heart compressing wall.

35. (New) A device according to claim 34 wherein said reinforcing material extends through the peripheral portions of the device into the heart compressing wall.

36. (New) A heart actuator device for use in heart assist apparatus, the device including a paddle-like main body, the main body including a heart compressing wall, which in use is adapted to be affixed to at least a region of the heart, and a distal wall, which in use is adapted to be distal that region of the heart, and the heart compressing wall being movable in a direction relatively away from the distal wall, so as, in use to compress at least that region of the heart thereby assisting movement of the heart wall, at least a portion of the heart compressing wall including a biointegratable material surface which facilitates the ingrowth of vascularised cellular tissue elements into the wall, the ingrowth of tissue into the heart compressing surface serving to affix the heart compressing wall of the main body to the heart.

37. (New) A device according to claim 36 wherein the distal wall includes a biointegratable material that promotes vascularised cellular growth into said distal wall so that it integrates into surrounding tissue.